

# GOATS



VERSATILITY



SPEED



### 5040 A/E Rim Clamp®

The 5040A/E is a highly capable, cost effective changer designed to service a variety of applications- including most OE fitments.

- Clamps wheels externally up to 21".
- 1.5 HP air drive or 1.0 HP Electric motor.
- Pedal activated X-shaped tabletop, clamps and bead loosener.
- Perfect choice for busy shops who require flexibility and volume.

**Speed:** Self centering clamps and bead loosening system add speed through simple operation.

**Accuracy:** Precision gauges mean accurate inflation, and our X-shaped tabletop provides the right clamping pressure for even the most delicate alloy wheels without damage.

**Durability:** Super-tough fiber reinforced composite air cylinders virtually never wear out. Bead loosener has extra support blocks for extra protection and durability.

**Ease of Use:** Foot controls are positioned for easy access. Built-in bead sealing jets and table top inflation simplify job completion.

# 5000 Series Tire Changers

Our 5000 Series Tire Changers are the workhorses of the tire service business. They're easy to use, incredibly durable, and fast.



### 5065 AX/EX Rim Clamp®

The 5065 AX/EX is the industry standard for tire service because of its speed, versatility, and value. You may also add an Inflation Guard for additional operator protection.

- Exclusive pedal-actuated X-shaped tabletop provides support for the most delicate wheels.
- Handles broad range of wheels and tires, from 6" to 26" in diameter and rims up to 14" wide.
- One-control manual swing arm adjusts horizontal tool head position while easy second control adjusts vertical height.
- 1.5 HP air drive system provides plenty of power plus infinite wheel control.
- Extra storage places everything at operator's fingertips.
- The extended tabletop services a broader range of wheels.
- Bead loosener has three support blocks for extra protection and durability.
- Built in bead sealing jets and tabletop inflation for faster work.
- Easy operation allows for fast training and high productivity.

## ACCESSORIES

See accessory catalog or web for more choices.



New extended reach Robo-Arm™ retrofit can make changing low profiles and runflats fast and almost effortless. (#85009943)



Bump-N-Roll saves time and effort in bead loosening by making it easy to put heavier wheels in place. (#8183491)



Bead loosener and lift tool socks help give you total alloy wheel protection from start to finish.



X-Out-clamps externally clamp wheels from 13 to 24 inches. (#8184327)



Optional inflation guard kit helps protect operator in case of tire explosions. (#8184177)

### HENNESSY INDUSTRIES, INC.

Manufacturer of Ammco®, Coats® and BADA® Automobile Service Equipment, Tools and Accessories.

1601 J.P. Hennessy Drive  
LaVergne, TN 37086-3565  
800-688-6496 or 615-641-7533

### Hennessy Canada

2430 Lucknow Drive, Unit #9  
Mississauga, Ontario L5S 1V3  
905-672-9440 Printed in USA.

[www.ammcoats.com](http://www.ammcoats.com)

Part No. 941065 Rev.5 05/09

Note: "A" designation = Air Drive "E" = Electric Drive  
"AX" = Air Drive/Extended Tabletop.  
"EX" = Electric Drive/Extended Tabletop.

## FEATURES to be compared

	5065 AX & EX	5040 A & E
<b>WHEELS HANDLED:</b> Alloy and steel	●	●
<b>MOUNT/DEMOUNT MECHANISM:</b> Manually swings away from wheel	●	●
<b>TOOL HEAD OFFSET:</b> Manual	●	●
<b>X-SHAPED TABLETOP:</b> For perimeter support of wheel	●	●
<b>EXTENDED TABLETOP:</b> For rims up to 22" external, 26" internal	●	
<b>CLAMPING:</b> Four wheel clamps actuated by 3-3/4" fiber/composite cylinder	●	●
<b>BEAD LOOSENING SYSTEM:</b> Foot control; handles wheels 2" to 12"		●
Foot control; handles wheels 2" to 17"	●	
<b>DRIVE SYSTEM OPTIONS:</b> 1.5 HP air drive	●	●
110v single phase-60 cycle electric drive	●	●
<b>PRESSURE LIMITER:</b> Standard	●	●
<b>BEAD SEATING RESERVOIR:</b> 3.8 gal. capacity in vertical tower	●	●
<b>INFLATION GAUGE:</b> Permanent in upper tower, 0 to 60 PSI	●	●
<b>AIR SUPPLY GAUGE (CAL OSHA):</b> 0 to 300 PSI	●	●
<b>WATER FILTER:</b> Standard	●	●
<b>STORAGE TRAY:</b> Standard	●	
Optional		●
<b>INFLATION GUARD SYSTEM:</b> Standard		
Optional	●	●

## SPECIFICATIONS

	5065 AX & EX	5040 A & E
Rim Diameter	6"-22" External; 8"-26" Internal	10"-21" External; 12"-24" Internal
Rim Width	14" Max	10-1/2" Max
Tire Diameter	50" Max	50" Max
Drive System	Air and Electric	Air and Electric
Air Source	110 to 175 PSI 14 to 15 SCFM @ 150 PSI	110 to 175 PSI 14 to 15 SCFM @ 150 PSI
Chassis Footprint	35"w x 44"d x 75"h	35"w x 44"d x 70"h
Shipping Weight	585 lbs.	585 lbs.

Specifications subject to change without notice. Units may not be exactly as pictured.